

2026 Pro Mini Car Rules

- FWD 112 RWD 108 WHEEL BASE
- No kickers or cradles all glass must be removed car must be stripped clean in and out gas tanks and battery must be moved inside car
- Motor aftermarket mounts and transmission mounts are allowed.
- Bumper aftermarket or homemade bumpers are allowed bumpers can be loaded.
- Core support can use 4x4 angle to the bottom of core support bottom only.
- Hood 6 locations for tie downs for hood.
- SUSPENSION Any wheel and tire combo solid struts and plated arms are allowed aftermarket ball joints are allowed aftermarket or reinforced tire rods are allowed.
- Body- struts towers can be welded or bolted body creasing is allowed trunks can be ditched body seams can be welded solid.
- Frame 8 plates no bigger than half inch fresh or prerun 12 inch bumper shocks 12 inches in or out 1 or the other not both can use 10 inch bumpers straps on top of Bumper must have 6 inch hole in trunk rear qtr does not have to be standing Frame seam welding k member is allowed all thread or chain from k member to frame 1 inch max all thread 3x5 or 4x4 plates with 1 inch gap in between plates.

- Cage 4 point cage with roll over bar and floating gas tank protector gas tank protector must stop before sheet metal cannot touch sheet metal 4 down bars can be used rear one has to be in line with rear seat bar front one has to be in line with front and dash bar back rear bar allowed 2 options option 1 sheet metal to sheet metal options 2 come off role over bar to gas tank protector 1 bar extending no more than 6 inches past speaker deck sheet metal to sheet metal must be secure, not floating.

Unlimited #9 wire